



# KTS1625

## Digital Multifunction Tester

(Insulation / Continuity / Loop / RCD / Voltage)

Safety and performance are two most critical requirements for every electrical system. The quality of insulation, properly working grounding system and active protection are “must have” to assure safety of the people, electrical systems and buildings against electrocution, fire, and other equipment damage. They are critical to prevent loss of productivity due to power interruption.

Robin-Amprobe KTS1625 is a multifunction installation tester measuring various parameters of the electrical system to provide complete safety analysis. It features loop impedance measurements as well as measurement of continuity and insulation resistance of motors, transformers or wires, testing of RCD systems, measuring voltage and frequency.

- **Insulation Function**
  - Selectable test voltages 250V, 500V and 1000V
- **Continuity Function**
  - Continuity test @ 200mA (short-circuit)
- **Line / Loop Impedance Functions**
  - Non Trip Loop test
  - Fast testing
  - Prospective earth fault current
  - Prospective short-circuit current
- **RCD Functions:**
  - Three levels of trip currents (X½, X1, X5) for complete range of testing applications
  - Phase switch selection 0° and 180° for positive and negative semi-cycle testing
  - RAMP slope measurement
  - Tests time-delayed RCD's (S-type)
  - RCD Half-Wave test
  - Auto RCD test
- Designed to allow testing to BS7671 IEE 17<sup>th</sup> Edition regulations
- Voltage and frequency measurements
- Instant correct wiring status check
- Dual measurement result display
- Large, backlit display
- Low battery indication
- Safety CAT III 300V

## KTS1625 Digital Multifunction Tester

## Data Sheet

### Specifications (At 23°C ± 5°C, 45% ~ 75% RH)

Insulation Resistance @ 250V/500V/1000V (Test Current ≥ 1mA)	0.00MΩ ~ 250MΩ @ 250V 0.00MΩ ~ 500MΩ @ 500V 0.00MΩ ~ 1000MΩ @ 1000V (Buzzer threshold: 2MΩ)	±(5% rdg + 5 LSD)
Continuity @ I <sub>N</sub> ≥ 200mA, U <sub>o</sub> =5Vdc (Nominal)	0.00Ω ~ 199Ω (Buzzer threshold: 20Ω)	±(2% rdg + 5 LSD)
Voltage Measurement	0V ~ 400V	±(5% rdg + 2 LSD) @ 45 to 65Hz / DC
Operating Test Voltage (Loop and RCD)	230Vac, 45Hz ~ 65 Hz	+10% to -15%
Line Impedance (L – N) @ 25A	0.01Ω ~ 1.99Ω / 19.9Ω / 0.20kΩ / 2.00kΩ	±(5% rdg + 5 LSD)
Loop Impedance (L – PE) @ 25A	0.01Ω ~ 1.99Ω / 19.9Ω / 0.20kΩ / 2.00kΩ	±(5% rdg + 5 LSD)
Loop Impedance without Tripping @ 15mA	0.01Ω ~ 1.99Ω / 19.9Ω / 0.20kΩ / 2.00kΩ	± (5% rdg + 12 LSD + Noise Margin (0.01 - 1.99Ω))
Prospective Short Circuit Current (PSC) @ 25A Prospective Earth Fault Current (PFC) @ 25A	0.00A ~ 1.99A / 2.0A ~ 19.9A / 20A ~ 199A / 200A ~ 1.99kA / 2.0kA ~ 26kA	PSC / PFC accuracy derived from measured loop impedance specification and measured voltage specification
RCD Test Current	10 / 30 / 100 / 300 / 500mA	0% to +10% @ 1Δn and 5Δn -10% to 0% @ ½Δn
RCD Trip Times @ X½	0 ~ 2000ms (10 / 30 / 100 / 300 / 500mA)	±(1% rdg + 2 ms)
RCD Trip Times @ X1 (selective)	0 ~ 500ms (10 / 30 / 100 / 300 / 500mA)	±(1% rdg + 2 ms)
RCD Trip Times @ X1	0 ~ 300ms (10 / 30 / 100 / 300 / 500mA)	±(1% rdg + 2 ms)
RCD Trip Times @ X5	0 ~ 40ms (10 / 30 / 100mA)	±(1% rdg + 2 ms)
RCD Auto Test	X½ / X1 / X5 (10 / 30 / 100mA)	Trip time: ±(1% rdg + 2 ms) Trip current: 0% to +10% @ 1Δn and 5Δn -10% to 0% @ ½Δn
RCD RAMP Test	X½ / X1 / X5 (10 / 30 / 100 / 300 / 500mA)	50% ~ 110% Default nominal residual currents (IΔn). Increasing by 10%, total 7 steps of residual current.
Fault Voltage Detection (N – PE conductor)	50Vac or more	
Operating Temperature	0°C to +40°C, ≤ 85% RH, no condensation	
Storage Temperature	-20°C to +60°C, ≤ 90% RH, no condensation (without batteries)	
Power Supply	1.5V Alkaline Battery (AA Battery) x 8 pcs	
Dimensions (L x W x H)	189 x 168 x 85 mm (7.43 x 6.65 x 3.35 in)	
Product Weight	Approx. 1.3 kg (2.87 lb) with batteries installed	
Regulation Compliance	Designed to allow testing to BS7671 IEE 17 <sup>th</sup> Edition regulations BS EN 61010-1 CAT III 300V BS EN 61557-1 / -2 / -3 / -4 / -6 / -10 BS EN 61326-1 (EMC)	
Included Accessories	3-Wires mains test cord set, test leads x 3, test probes x 3, alligator clips x 3, test probe with remote test button, batteries ( 8 x AA), users manual, strap and carrying case	



### Robin-Amprobe® Test Tools UK

52 Hurricane Way, Norwich,  
Norfolk, NR6 6JB, United Kingdom

Web: [www.robin-amprobe.co.uk](http://www.robin-amprobe.co.uk)

Email: [info@robin-amprobe.co.uk](mailto:info@robin-amprobe.co.uk)

Phone: +44 (0) 1603 25 6662

Fax: +44 (0) 1603 25 6664

©2011 Robin-Amprobe® Test Tools UK. All rights reserved.  
11/2011 KTS1625 Rev A